



PINS 4 PINS

5 PINS

7 PINS

FIRER SIZE 0.010"

0.019"

THE REAL #1
ANYONE CAN CLAIM IT. WE PROVE IT!

RHEOSTAT COVER

ADJUST FIBER BRIGHTNESS & ELIMINATE STARBUST

3RD AXIS ADJUSTMENT

2ND AXIS ADJUSTMENT

GEAR TOOTH LOCK KNOBS ADJUST WHERE YOU WANT IT

AMBIDEXTROUS RH/LH



- MICRO-ADJUST WINDAGE & ELEVATION KNOBS
- AIMING RING & PIN AT SAME DEPTH FOR ACCURACY
- STRONGER BRIGHTER FIREPIN WITH 18" OF FIBER PER PIN
- LEVEL VIAL INSIDE SCOPE FOR ARROW CLEARANCE
- INDIVIDUAL MICRO ADJUSTABLE PINS






WARNING: This product can expose you to chemicals including Nickel Acetate, which is known to the State of California to cause cancer or birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov.



🕇 🚵 🛂 😾 We Make Arckery Better!

WWW.AXCELSIGHTS.COM





TO GAIN MORE WINDAGE & ELEVATION

REMOVE SCREWS (E) AND LOCATE ALIGNMENT HOLES TO PROVIDE MORE OR LESS WINDAGE & ELEVATION TRAVEL.

TO ADJUST 2ND AXIS

LOOSEN SCREWS (E) ADJUST SCOPE TO LEVEL AND THEN RETIGHTEN SCREWS. INSURE BUBBLE VIAL IS LEVEL AFTER TIGHTENING.

TO ADJUST 3RD AXIS

AFTER 2ND AXIS ADJUSTMENT AND WHILE BOW IS IN LEVEL POSITION, TILT 45° DOWNWARD IN BOW VISE. LOOSEN SCREWS (F) & (G). THEN SNUG SCREW (F) AND HINGE SCOPE UNTIL LEVEL, THEN TIGHTEN SCEWG. INSURE BOTH SCREWS ARE TIGHT AND SCOPE IS LEVEL IN BOTH 2ND AND 3RD AXIS.

INDIVIDUAL MICRO-PIN ADJUSTMENT

TO MOVE SINGLE SIGHT PIN OR MORE THAN ONE PIN AT THE SAME TIME. USE SUPPLIED 5/64" HEX WRENCH TO LOOSEN DESIRED SIGHT PIN SCREWS 2-TURNS COUNTERCLOCKWISE. TURN MICRO-ADJUST KNOB (D) TO MOVE DESIRED SIGHT PIN/PINS UP OR DOWN, RE-TIGHTEN SIGHT PIN SCREWS HOLDING SHORT END OF SUPPLIED HEX WRENCH.

MATHEWS® HARMONIC

DAMPER AVAILABLE

WARNING: DO NOT OVERTIGHTEN SIGHT PINS!

WARNING: TO AVOID OVER-TIGHTENING SIGHT PINS, HOLD SHORT END OF WRENCH



GEAR TOOTH WINDAGE & ELEVATION THUMB LOCKS REMOVE SCREW ON TOP OF THUMB LOCKS (A1) & (A2)

> PLACE ON DESIRED TOOTH LOCATION. RETIGHTEN. ELEVATION ADJUSTMENT: LOOSEN THUMB LOCK (A2) CLICK ELEVATION KNOB B CLOCKWISE TO MOVE ARROW UP ON TARGET, COUNTERCLOCKWISE TO MOVE ARROW DOWN ON TARGET. TURN THUMB LOCK CLOCKWISE UNTIL

TIGHT TO KEEP ELEVATION FROM MOVEMENT. WINDAGE ADJUSTMENT: LOOSEN THUMB LOCK (A1) AND CLICK WINDAGE KNOB (C) CLOCKWISE TO MOVE ARROW RIGHT ON TARGET, COUNTERCLOCKWISE TO MOVE ARROW LEFT ON TARGET. TURN THUMB LOCK CLOCKWISE UNTIL TIGHT TO



LIGHT MOUNTING HOLF 3/8" x 32 THREAD SIGHT LIGHT SOLD SEPARATELY

LEGAL

ITEMS IN THIS PACKAGING MAY BE PATENT PENDING OR COVERED BY US PATENTS & REGISTERED TRADEMARKS. VISIT

WWW.AXCELSIGHTS.COM/LEGAL.HTML FOR A FULL LIST OF PATENTS & TRADEMARKS.

AXCEL SIGHTS - 131 Crennel Dr. - PO Box 1180 Madison Heights, VA 24572 - 434-929-2800 - info@axcelsights.com

LIMITED LIFETIME WARRANTY

THIS AXCIEL SIGHT IS GUARANTEED ONLY TO THE ORIGINAL OWNER, WITH A VALID SALES RECEIPT, AGAINST DEFECTS IN MATERIALS AND WORKMANSHIP NOT CAUSED BY NORMAL WEAR FOR THE LIFETIME OF THE PRODUCT. FIBER OPTIC BREAKAGE OR MODIFICATION IS NEVER COVERED UNDER WARRANTY. T.R.U. INC., THE MANUFACTURER OF AXCEL SIGHTS, RESERVES THE RIGHT TO REPAIR OR REPLACE DEFECTIVE PARTS AT ITS DISCRETION. IN THE EVENT OF BREAKAGE DUE TO DEFECTIVE PARTS, THE LIABILITY OF T.R.U. INC. SHALL NEVER EXCEED THE ORIGINAL RETAIL COST OF THE PRODUCT. DEFECTS CAUSED BY NORMAL WEAR MAY BE REPAIRED FOR AN ADDITIONAL CHARGE.

> RHEOTECH (AXRT-D519-BK) Dampened / 5 Pins / .019 Fibers / Black

